

Patent Abstracts of Japan

PUBLICATION NUMBER : 11191987
 PUBLICATION DATE : 13-07-99


APPLICATION DATE : 02-06-98
 APPLICATION NUMBER : 10152809

APPLICANT : OKUMA CORP;

INVENTOR : NASHIKI MASAYUKI;

INT.CL. : H02P 5/05 H02K 19/10

TITLE : SWITCHED RELUCTANCE MOTOR



ABSTRACT : PROBLEM TO BE SOLVED: To attain a switch reluctance motor with a small torque ripple, control device, and high-speed rotary operation thereof.

SOLUTION: In a switched reluctance motor and its control device, the switched reluctance motor is provided with a switched reluctance motor(NORM) that has six stator protrusion poles with a width of approximately 30 degrees, four rotor protrusion poles with a width of approximately 50 degrees, and excitation coil winding wound around each stator protrusion pole and connected in series, an excitation drive means (FCC and FD) that connects each excitation coil winding in series and supplies a DC excitation current (ID) to each excitation coil winding for exciting the motor in accordance with an excitation command signal (FCM), and a torque current drive means (PW) that successively energizes current with a quantity in accordance with a torque command(TCM) to the torque coil winding of six stator magnetic poles corresponding to the angle of the rotation of a rotor.

COPYRIGHT: (C)1999,JPO